

CT 5800

CATERING TRUCK



VAN BODY

The steel constructed body is covered with insulation material filled polyester plates. The van-body is lifted by a scissors system powered by two single acting telescopic hydraulic cylinders. The van-body provides a lock system for trolleys mounted the side walls. Adequate ventilation is provided inside the van body. The van body provides front/rear roller doors.

FRONT PLATFORM

The front platform is produced by steel profiles and is hot dip galvanized. It moves with van body to serve the aircraft. The front platform provides an extendible part moved by a hydraulic cylinder and an access bridge which moves longitudinally along the front platform. The floor is covered with checkered aluminum.

TRUCK

Subject to customer's demand.

HYDRAULIC SYSTEM

The hydraulic system is provided by an oil tank, a pump driven by truck engine, cylinders, lock valves, hydraulic valves and some useful accessories. Emergency hand pump is also used in case of engine failure. 4 hydraulic stabilizers are provided for more stability.

SURFACES

The platform and the tail lift is hot dip galvanized and the other parts are custom painted.

LIGHTING

LED type lighting fixtures, headlamps in front and rear of the platform, gabary lamps at the corners and a beacon are provided on the van body.

OPTIONS

Tail lift, canopy, electrical emergency pump, cooling system for van body and the driver cab, side door, emergency stair, custom painting, logo application.



www.timsan-gse.com

Eyüp Sultan Mh. Kartopu Sk. No.7

Sancaktepe, İstanbul, Turkey

+90 216 527 4270